



## Declaration of Performance

DoP-No. 528100000

- |   |   |
|---|---|
| 1. Product name                                     | Tecryl  |
| 2. Type of product                                  | Acrylic sealant   |
| 3. Application                                      | Sealant for the application in facades<br>Type F EXT-INT 7,5P   |
| 4. Manufacturer                                     | Novatech International NV<br>Industrielaan 5 B<br>BE-2250 Olen<br>T. +32 14 85 97 37<br>F. +32 15 85 97 38<br>E. <a href="mailto:info@tec7.com">info@tec7.com</a> |
| 5. Representative                                   | not applicable  |
| 6. System of assessment of constancy of performance | System 3 / reaction to fire: System 3   |
| 7. Harmonised Standard                              | EN 15651-1: 2012-12   |
| 8. Notified body                                    | SKZ-TECONA GmbH, NB 1213, performed the product type testing and the reaction to fire and issued the test report.   |

### 9. Essential characteristics

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1: 2012-12
Release of chemicals dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
a) Resistance to flow	≤ 3 mm	
b) Loss of volume	≤ 25 %	
c) Tensile properties at maintained extension after water immersion	≤ 25 %	
d) Durability	pass	

NPD: No performance determined

\*: please consult the safety data sheet

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Novatech International NV  
Represented by  
Novatio Invest NV  
Delegated Representative  
Mr. Bert Vissers

Olen, 23 May 2018